



DRILCORP

DCR 4 EGT-VD710_3

TYPICAL APPLICATIONS

INDEPENDENT
WATER
SUPPLY

GEOTHERMAL
CLIMATE
CONTROL

DEWATERING

CORING
APPLICATIONS

SPECIFICATION

DRILLING TORQUE (CLOCKWISE)	4550 KGM
ROTATION SPEED (CLOCKWISE)	603 RPM
MAX PULL BACK FORCE	9000KG
MAX STROKE	3400 MM
MAIN WINCH – MAX DIRECT PULL	2000 KG
WIRE LINE WINCH MAX DIRECT PULL	1500KG
GROUND PRESSURE	0,071 MPA
TYPICAL NOISE LEVELS AT 1 M	74 DBA

KEY FEATURES

- VERSATILE MAST FOR ANGLE DRILLING
- REMOTE CONTROLLED FOR SAFETY
- RUBBER TRACKED FOR MINIMUM ROAD DAMAGE BUILT IN WIRE LINE WINCH
- FITTED MIST AND JET WASH PUMPS

OVERALL DIMENSIONS

	TRAVELLING	OPERATIONAL
HEIGHT	2808 MM	7800 MM
LENGTH	7800 MM	5169 MM
WIDTH	1600 MM	1600 MM

GROSS WEIGHT 8000 KG



DRILCORP

DCR 4
EGT-VD710_3

TECHNICAL DRAWING

VD710_3

This is  equipment

