



DRILCORP

**DCR 2
DCR 17
MASSENZA
MI6**

TYPICAL APPLICATIONS

INDEPENDENT
WATER
SUPPLY

GEOTHERMAL
CLIMATE
CONTROL

DEWATERING

ENVIRONMENTAL
SOIL SAMPLING

SPECIFICATION

| | |
|-----------------------------|-------------|
| MAX TORQUE | 8560 NM |
| ROTATION SPEED | 0 – 500 RPM |
| DRILLING DIAMETER | 406 MM |
| MAX CLAMPING DIAMETER | 360 MM |
| MAX PULLBACK FORCE | 56 kN |
| MAX STROKE | 3,700 MM |
| WINCH – MAX DIRECT PULL | 20 kN |
| DRIVE TRACKED | RUBBER |
| GROUND PRESSURE | 2.27 kN/M2 |
| TYPICAL NOISE LEVELS AT 1 M | 74 DBA |

KEY FEATURES

- FOLD AWAY MAST FOR RESTRICTED SITES
- REMOTE CONTROLLED FOR TRACKING FOR SAFETY
- RUBBER TRACKED FOR MINIMUM DAMAGE TO ROADS
- BUILT IN LUBRICATION FOR HAMMERS
- MIST AND JET WASH PUMPS

OVERALL DIMENSIONS

| | TRAVELLING | OPERATIONAL |
|--------|------------|-------------|
| HEIGHT | 2,704 MM | 8,470 MM |
| LENGTH | 5,914 MM | 5,014 MM |
| WIDTH | 1,810 MM | 1,810 MM |

GROSS WEIGHT 6,750 KG



DRILCORP

DCR 17&2 MASSENZA MI6

TECHNICAL DRAWING

